NSN 5915-01-342-3385

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-342-3385

Overall Length: 2.480 inches **Body Length:** 1.150 inches **Body Outside Diameter:** 0.250 inches Vibration Resistance Range In Hertz: +10.0/+2000.0 **Operating Tempurature Range:** -54.0/+85.0 degrees celsius **Reference Frequency Per Function:** 17.0 gigahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Voltage Standing Wave Ratio Per Function:** 1.5 blank **Average Power Rating Per Function:** 2.0 watts blank **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 2 terminal **Features Provided:** Moisture resistant and shock resistant Insertion Loss At Reference Frequency Per Function In Decibels: 2.0 blank **Functional Terminal Type And Quantity:** 1 connector, receptacle input 1st function1 connector, plug output 2nd function **Specified Frequencies Of Discrimination Per Function:** 8.00 gigahertz blank and 17.00 gigahertz blank and 17.50 gigahertz blank and 26.00 gigahertz blank **Body Material:** Aluminum **Frequency Band Width Per Function:** 8.00 gigahertz blank and 17.00 gigahertz blank Discrimination At Specificationified Frequencies Per Function In Decibels: 4.0 blank and 35.0 blank

8.0 gigahertz blank and 17.0 gigahertz blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

NSN 5915-01-342-3385

Low Pass Filter - Page 2 of 2



Body Surface Treatment:
Silver
Unpackaged Unit Weight:
0.700 ounces
Precious Material And Location:
Body surfaces silver
Precious Material:
Silver
Style Designator:
Round terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A047b0