

View Online at <https://aerobasegroup.com/nsn/5915-01-342-6726>

Body Outside Diameter:

1.250 inches

Body Height:

0.625 inches

End Application:

5895-01-233-2919communication system control group

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference60.0 2nd radio interference60.0 3rd radio interference60.0 4th radio interference60.0 5th radio interference60.0 6th radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference3.0 2nd radio interference3.0 3rd radio interference3.0 4th radio interference3.0 5th radio interference3.0 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 threaded hole

Functional Terminal Type And Quantity:

1 pin input 1st function1 pin output 2nd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function and 200.0 volts dc 1st radio interference 1st function115.0 volts ac 2nd radio interference 2nd function and 200.0 volts dc 2nd radio interference 2nd function115.0 volts ac 3rd radio interference 3rd function and 200.0 volts dc 3rd radio interference 3rd function115.0 volts ac 4th radio interference 4th function and 200.0 volts dc 4th radio interference 4th function115.0 volts ac 5th radio interference 5th function and 200.0 volts dc 5th radio interference 5th function115.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function

Thread Size:

0.112 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Special Features:

40 filtered contacts

Style Designator:

Round terminal/terminals on one surface

Fig:

A047b0