

View Online at <https://aerobasegroup.com/nsn/5915-01-342-6728>

Overall Length:

6.070 inches

Body Length:

5.000 inches

Body Width:

3.000 inches

Body Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Operating Temperature Range:

+0.0/+50.0 degrees celsius

End Application:

5895-01-280-3568 communication set

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

400.0 1st radio interference400.0 2nd radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference3.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.15 volts ac 1st radio interference1.15 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms3113h12c3p

Maximum Temperature Rise:

50.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 threaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function2 threaded stud output 2nd function1 threaded stud ground 3rd function

Operating Voltage Rating And Type Per Function:

115.0 volts ac 1st radio interference 1st function115.0 volts ac 2nd radio interference 2nd function

Thread Size:

0.190 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

550.0 volts at sea level

Special Features:

Two filtered functions

Unpackaged Unit Weight:

2.100 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0