

View Online at <https://aerobasegroup.com/nsn/5915-01-343-2392>

Overall Height:

0.650 inches

Body Length:

1.000 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

End Application:

Mx10407 anlzr

Reference Frequency Per Function:

60.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.25 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

1.25 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function 4 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

12.50 megahertz blank and 50.00 megahertz blank and 70.00 megahertz blank and 107.50 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

50.00 megahertz blank and 70.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

50.0 megahertz blank and 70.0 megahertz blank

Body Surface Treatment:

Gold

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0