

View Online at <https://aerobasegroup.com/nsn/5915-01-343-2396>

Overall Height:

1.005 inches

Body Length:

2.370 inches

Body Width:

1.000 inches

Body Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.000 inches

Vibration Resistance Range In Hertz:

+5.0/+1000.0

End Application:

Mx10407 anlzr

Reference Frequency Per Function:

75.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

2.0 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

8.0 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function 3 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

74.95 megahertz blank and 74.955 megahertz blank and 75.045 megahertz blank and 75.05 megahertz blank

Thread Size:

0.112 inches

Body Material:

Metal

Frequency Band Width Per Function:

74.955 megahertz blank and 75.045 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

74.955 megahertz blank and 75.045 megahertz blank

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0