

View Online at <https://aerobasegroup.com/nsn/5915-01-343-2400>

Overall Height:

0.650 inches

Body Length:

1.500 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.600 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

End Application:

Mx10407 analyzer

Reference Frequency Per Function:

260.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.25 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

7.5 blank

Functional Terminal Type And Quantity:

1 pin input 1st function1 pin output 2nd function6 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

246.00 megahertz blank and 253.50 megahertz blank and 266.50 megahertz blank and 274.00 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

253.50 megahertz blank and 266.50 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

253.5 megahertz blank and 266.5 megahertz blank

Body Surface Treatment:

Gold

Precious Material And Location:

Boby surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0