

View Online at <https://aerobasegroup.com/nsn/5915-01-343-2848>

Overall Height:

0.650 inches

Body Length:

1.500 inches

Body Width:

0.500 inches

Body Height:

0.400 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.673 inches

End Application:

Mx10407 anlzr

Reference Frequency Per Function:

300.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.25 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded stud

Insertion Loss At Reference Frequency Per Function In Decibels:

7.5 blank

Functional Terminal Type And Quantity:

1 pin input 1st function1 pin output 2nd function6 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

299.984 megahertz blank and 299.9925 megahertz blank and 300.0075 megahertz blank and 300.016 megahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

299.9925 megahertz blank and 300.0075 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

175.5 megahertz blank and 184.5 megahertz blank

Body Surface Treatment:

Gold

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0