

View Online at <https://aerobasegroup.com/nsn/5915-01-343-8388>

**Body Outside Diameter:**

0.360 inches

**Body Height:**

0.250 inches

**End Application:**

Mx10407 anlzr

**Reference Frequency Per Function:**

30.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.25 blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

3 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

2.6 blank

**Functional Terminal Type And Quantity:**

1 pin input 1st function 1 pin output 2nd function 1 pin ground 3rd function

**Specified Frequencies Of Discrimination Per Function:**

30.0235 megahertz blank and 29.997 megahertz blank and 30.003 megahertz blank and 29.9765 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

29.997 megahertz blank and 30.003 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

29.997 megahertz blank and 30.003 megahertz blank

**Body Surface Treatment:**

Gold

**Precious Material And Location:**

External surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Round terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0