

View Online at <https://aerobasegroup.com/nsn/5915-01-344-0135>

Body Outside Diameter:

0.360 inches

Body Height:

0.250 inches

End Application:

Mx10407 anlzr

Reference Frequency Per Function:

210.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.25 blank

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

3 terminal

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function 1 pin ground 3rd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 210.00 megahertz blank and 370.00 megahertz blank and 740.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.00 megahertz blank and 210.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 30.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.0 megahertz blank and 210.0 megahertz blank

Body Surface Treatment:

Gold

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Style Designator:

Round terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0