

View Online at <https://aerobasegroup.com/nsn/5915-01-344-2407>

Overall Length:

1.719 inches

Overall Height:

1.438 inches

Overall Width:

1.438 inches

Mounting Slot Width:

0.128 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

F110ge129engi

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Operating Current Rating Per Function In Amps:

3.0 1st radio interference3.0 2nd radio interference3.0 3rd radio interference3.0 4th radio interference3.0 5th radio interference3.0 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

4 slot

Functional Terminal Type And Quantity:

32 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

800.0 volts dc 1st radio interference 1st function800.0 volts dc 2nd radio interference 2nd function800.0 volts dc 3rd radio interference 3rd function800.0 volts dc 4th radio interference 4th function800.0 volts dc 5th radio interference 5th function800.0 volts dc 6th radio interference 6th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2.0 kilovolts at sea level

Body Surface Treatment:

Tin

Special Features:

32 filtered functions

Style Designator:

Filter connector

Shelf Life:

Demilitarization:

No

Fiig:

A047b0