NSN 5915-01-344-4630

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-344-4630 **Overall Length:** 1.510 inches **Body Length:** 0.750 inches **Body Width:** 0.500 inches **Body Height:** 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.630 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.380 inches **Operating Tempurature Range:** -54.0/+60.0 degrees celsius **End Application:** F15 aircraft **Reference Frequency Per Function:** 4.2 gigahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank **Load Impedance Per Function:** 50.0 ohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Voltage Standing Wave Ratio Per Function:** 1.5 blank **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Encased **Mounting Facility Type And Quantity:** 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank **Functional Terminal Type And Quantity:** 1 connector, receptacle input 1st function1 connector, receptacle output 2nd function **Specified Frequencies Of Discrimination Per Function:** 9.00 megahertz blank and 4.20 gigahertz blank and 5.554 gigahertz blank and 7.28 gigahertz blank **Thread Size:** 0.060 inches **Body Material:**

Metal

NSN 5915-01-344-4630

Low Pass Filter - Page 2 of 2



Frequency Band Width Per Function:

9.00 megahertz blank and 4.20 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 12.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

9.0 megahertz blank and 4.2 gigahertz blank

Unpackaged Unit Weight:

0.350 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0