## NSN 5915-01-344-4932

8.00 gigahertz blank and 13.00 gigahertz blank

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-344-4932

Overall Length:
2.070 inches
Body Length:
1.310 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.112 inches
Operating Tempurature Range:
-54.0/+60.0 degrees celsius
End Application:
F15 aircraft
Reference Frequency Per Function:
13.0 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.75 blank
Mounting Facility Screw Thread Series Designator:
Unc
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
2 threaded hole
Insertion Loss At Reference Frequency Per Function In Decibels:
1.0 blank
Functional Terminal Type And Quantity:
1 connector, receptacle input 1st function1 connector, receptacle output 2nd function
Specified Frequencies Of Discrimination Per Function:
6.80 gigahertz blank and 8.00 gigahertz blank and 13.00 gigahertz blank and 14.00 gigahertz blank
Thread Size:
0.086 inches
Body Material:
Metal
Frequency Band Width Per Function:

## NSN 5915-01-344-4932

Band Pass Filter - Page 2 of 2



## Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:** 

8.0 gigahertz blank and 13.0 gigahertz blank

**Unpackaged Unit Weight:** 

4.200 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A047b0