

View Online at <https://aerobasegroup.com/nsn/5915-01-345-2287>

Overall Length:

0.643 inches

Body Length:

0.350 inches

Vibration Resistance Range In Hertz:

+4.0/+33.0

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Operating Current Rating Per Function In Amps:

3.0 blank

Maximum Voltage Drop Per Function:

3.0 volts dc blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

85.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.0 and 0.1 and 1.0 and 10.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

3.0 and 5.0 and 5.0 and 15.0 and 35.0 and 35.0

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Width Across Flats:

0.156 inches

Mounting Facility Type And Quantity:

1 threaded stud

Functional Terminal Type And Quantity:

1 pin input 1st function 1 pin output 2nd function

Operating Voltage Rating And Type Per Function:

300.0 volts dc blank

Thread Size:

0.112 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

600.0 volts at sea level

Body Surface Treatment:

Silver

Precious Material And Location:

Body and contact surfaces silver

Precious Material:

Silver

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0