NSN 5915-01-346-0788

Band Pass Filter - Page 1 of 2

4 threaded hole



View Online at https://aerobasegroup.com/nsn/5915-01-346-0788

Overall Length:
3.250 inches
Body Length:
2.498 inches
Body Width:
0.660 inches
Body Height:
0.610 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.838 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.480 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
End Application:
F-15/56c ste
Reference Frequency Per Function:
10.0 gigahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Input Terminal Manufacturer Code:
81413
Input Terminal Identification:
Mil-c-39012
Output Terminal Manufacturer Code:
81413
Output Terminal Identification:
Mil-c-39012
Voltage Standing Wave Ratio Per Function:
1.5 blank
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
4 threaded hale

NSN 5915-01-346-0788

Band Pass Filter - Page 2 of 2



Features Provided: Nut and washer Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank **Functional Terminal Type And Quantity:** 1 connector, receptacle input 1st function1 connector, receptacle output 2nd function **Specified Frequencies Of Discrimination Per Function:** 9.71 gigahertz blank and 9.96 gigahertz blank and 10.04 gigahertz blank and 10.29 gigahertz blank Thread Size: 0.086 inches **Body Material:** Metal **Frequency Band Width Per Function:** 9.96 gigahertz blank and 10.04 gigahertz blank **Discrimination At Specificationified Frequencies Per Function In Decibels:** 1.0 blank and 50.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function: 9.96 gigahertz blank and 10.04 gigahertz blank **Style Designator:** Rectangular terminal/terminals on opposite surfaces Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A047b0 Mil-std (military Standard): Mil-c-39012 spec.