

View Online at https://aerobasegroup.com/nsn/5915-01-346-8668

Overall Length:
1.418 inches
Body Length:
0.874 inches
Body Outside Diameter:
0.702 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
End Application:
Asge426 ser s
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
400.0 blank
Operating Current Rating Per Function In Amps:
10.0 blank
Maximum Voltage Drop Per Function:
1.25 volts screw on tube not specified and 1.5 volts 23rd band suppression not specified
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Maximum Tempurature Rise:
25.0 degrees celsius
Mounting Facility Screw Thread Series Designator:
Unf
Inclosure Type:
Hermetically sealed
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Nut and washer
Functional Terminal Type And Quantity:
1 tab, solder lug input 1st function1 tab, solder lug output 2nd function
Operating Voltage Rating And Type Per Function:
125.0 volts ac blank and 150.0 volts dc blank
Thread Size:
0.312 inches
Body Material:
Metal



Maximum Dielectric Withstanding Dc Voltage:

375.0 volts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A047b0