

View Online at <https://aerobasegroup.com/nsn/5915-01-346-8668>

Overall Length:

1.418 inches

Body Length:

0.874 inches

Body Outside Diameter:

0.702 inches

Vibration Resistance Range In Hertz:

+10.0/+500.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Asge426 ser s

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

10.0 blank

Maximum Voltage Drop Per Function:

1.25 volts screw on tube not specified and 1.5 volts 23rd band suppression not specified

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Nut and washer

Functional Terminal Type And Quantity:

1 tab, solder lug input 1st function 1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 150.0 volts dc blank

Thread Size:

0.312 inches

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

375.0 volts at sea level

Style Designator:

Round terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0