

View Online at <https://aerobasegroup.com/nsn/5915-01-346-8669>

**Overall Length:**

19.375 inches

**Body Length:**

12.250 inches

**Body Width:**

7.125 inches

**Body Height:**

3.563 inches

**Vibration Resistance Range In Hertz:**

+10.0/+500.0

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

250.0

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 1st radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 1st radio interference 400.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

20.0 1st radio interference 20.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

2.5 volts ac 1st radio interference and 6.0 volts dc 1st radio interference 2.5 volts ac 2nd radio interference and 6.0 volts dc 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 terminal

**Features Provided:**

Nut and washer

**Functional Terminal Type And Quantity:**

2 threaded stud input 1st function 2 threaded stud output 2nd function

**Operating Voltage Rating And Type Per Function:**

250.0 volts ac 1st radio interference 1st function and 600.0 volts dc 1st radio interference 1st function 250.0 volts ac 2nd radio interference 2nd function and 600.0 volts dc 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

1.2 kilovolts at sea level

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0