

View Online at <https://aerobasegroup.com/nsn/5915-01-347-1580>

Overall Length:

2.610 inches

Overall Height:

3.715 inches

Body Length:

1.470 inches

Body Width:

2.500 inches

Body Height:

2.500 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Operating Temperature Range:

-40.0/+85.0 degrees celsius

End Application:

5865-01-299-5859

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference

Operating Current Rating Per Function In Amps:

60.0 1st radio interference 20.0 2nd radio interference 80.0 3rd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference

Input Terminal Manufacturer Code:

96906

Input Terminal Identification:

Ms17348r24c12p

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded stud

Features Provided:

Moisture resistant and shock resistant

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 3 turret output 2nd function 1 turret ground 3rd function and 1 threaded stud ground 3rd function

Operating Voltage Rating And Type Per Function:

28.0 volts ac 1st radio interference 1st function 28.0 volts dc 2nd radio interference 2nd function 50.0 volts dc 2nd radio interference 3rd function

Thread Size:

0.190 inches

Body Material:

Metal

Body Surface Treatment:

Tin

Special Features:

Three filtered functions; six unfiltered functions

Style Designator:

Rectangular terminal/terminals on three surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0