

View Online at <https://aerobasegroup.com/nsn/5915-01-347-1841>

Overall Length:

2.640 inches

Body Length:

1.880 inches

Body Width:

0.950 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.675 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-54.0/+60.0 degrees celsius

End Application:

F15 aircraft

Reference Frequency Per Function:

3.3214 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

50140

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

50140

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 threaded hole

Features Provided:

Fungus resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.8 blank

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

3.113 gigahertz blank and 3.2414 gigahertz blank and 3.4014 gigahertz blank and 3.513 gigahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

3.2414 gigahertz blank and 3.4014 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 40.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

3.2414 gigahertz blank and 3.4014 gigahertz blank

Body Surface Treatment:

Tin

Special Features:

F15 aircraft

Unpackaged Unit Weight:

7.500 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0