NSN 5915-01-347-2737

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-347-2737

Overall Length:
14.880 inches
Body Length:
12.880 inches
Body Width:
3.750 inches
Body Height:
3.750 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Operating Tempurature Range:
-54.0/+52.0 degrees celsius
End Application:
5411-01-304-6121 shelter, nonexpa
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Power Line Frequency Rating Per Function In Hertz:
60.0 blank
Operating Current Rating Per Function In Amps:
10.0 blank
10.0 blank
10.0 blank Maximum Voltage Drop Per Function:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded stud
10.0 blank Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded stud Features Provided:
Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded stud Features Provided: Nut and washer
Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded stud Features Provided: Nut and washer Functional Terminal Type And Quantity:
Maximum Voltage Drop Per Function: 1.2 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Maximum Tempurature Rise: 25.0 degrees celsius Mounting Facility Screw Thread Series Designator: Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 1 threaded stud Features Provided: Nut and washer Functional Terminal Type And Quantity: 1 threaded stud input 1st function1 threaded stud output 2nd function

Thread Size:

0.375 inches

NSN 5915-01-347-2737

Radio Frequency Interference Filter - Page 2 of 2



Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
240.0 volts at sea level
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A047b0