

View Online at <https://aerobasegroup.com/nsn/5915-01-350-0736>

Overall Length:

9.420 inches

Body Length:

8.320 inches

Body Width:

4.220 inches

Body Height:

1.720 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.870 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Operating Temperature Range:

-45.0/+49.0 degrees celsius

End Application:

5895-01-316-2747

Reference Frequency Per Function:

30.0 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Input Terminal Manufacturer Code:

95105

Input Terminal Identification:

Sma-receptacle

Output Terminal Manufacturer Code:

95105

Output Terminal Identification:

Sma-receptacle

Voltage Standing Wave Ratio Per Function:

1.6 blank

Average Power Rating Per Function:

1.5 kilowatts blank

Inclosure Type:

Encased

Output Voltage Rating:

50.0 ac volts

Mounting Facility Type And Quantity:

4 unthreaded hole

Features Provided:

Active and fungus resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

3.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.00 hertz blank and 1.60 megahertz blank and 30.00 megahertz blank and 60.00 megahertz blank

Body Material:

Metal

Frequency Band Width Per Function:

1.60 megahertz blank and 30.00 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

1.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.6 megahertz blank and 30.0 megahertz blank

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A047b0