

View Online at <https://aerobasegroup.com/nsn/5915-01-350-5428>

**Overall Length:**

2.810 inches

**Overall Height:**

1.160 inches

**Overall Width:**

3.360 inches

**Body Length:**

2.070 inches

**Body Width:**

2.860 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.360 inches and 2.390 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

3b15-401

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

50.0 1st radio interference 50.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

20.0 1st radio interference 20.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Features Provided:**

Mounting bracket

**Functional Terminal Type And Quantity:**

2 tab, solder lug input 1st function 2 tab, solder lug output 2nd function 1 tab, solder lug ground 3rd function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function 50.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

2.25 kilovolts at sea level

**Special Features:**

Two filtered functions

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0