NSN 5915-01-350-6599

Band Pass Filter - Page 1 of 2

Overall Height: 0.700 inches Body Length:



View Online at https://aerobasegroup.com/nsn/5915-01-350-6599

| 2.000 inches |
|--|
| Body Width: |
| 2.000 inches |
| Body Height: |
| 0.500 inches |
| Operating Tempurature Range: |
| +0.0/+70.0 degrees celsius |
| End Application: |
| Generator ref |
| Reference Frequency Per Function: |
| 3.125 kilohertz blank |
| Source Impedance Rating Per Function: |
| 10.0 ohms blank |
| Load Impedance Per Function: |
| 100.0 ohms blank |
| Principal Circuitry Type Per Function: |
| Inductance-capacitance blank |
| Inclosure Type: |
| Encased |
| Output Voltage Rating: |
| 5.0 dc volts |
| Mounting Facility Type And Quantity: |
| 6 terminal |
| Features Provided: |
| Active and butterworth response |
| Insertion Loss At Reference Frequency Per Function In Decibels: |
| 3.0 blank |
| Functional Terminal Type And Quantity: |
| 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function |
| Specified Frequencies Of Discrimination Per Function: |
| 2.60 kilohertz blank and 3.65 kilohertz blank |
| Body Material: |
| Metal |
| Frequency Band Width Per Function: |
| 2.719 kilohertz blank and 3.531 kilohertz blank |
| Discrimination At Specificationified Frequencies Per Function In Decibels: |
| 3.0 blank and 40.0 blank |
| Body Surface Treatment: |
| Tin |

NSN 5915-01-350-6599

Band Pass Filter - Page 2 of 2



| Special Features: |
|--------------------------|
| Two unfiltered terminals |

i wo diffillered terrifila

Style Designator:Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0