NSN 5915-01-350-7391

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-350-7391

View Online at https://aerobasegroup.com/nsn/5915-01-350-7391
Overall Height:
0.700 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
0.500 inches
Vibration Resistance Range In Hertz:
+10.0/+500.0
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Reference Frequency Per Function:
50.0 kilohertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Inclosure Type:
Inclosure Type: Encased
Encased
Encased Output Voltage Rating:
Encased Output Voltage Rating: 5.0 dc volts
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material: Metal
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material: Metal Frequency Band Width Per Function:
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material: Metal Frequency Band Width Per Function: 49.188 kilohertz blank and 50.812 kilohertz blank
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material: Metal Frequency Band Width Per Function: 49.188 kilohertz blank and 50.812 kilohertz blank
Encased Output Voltage Rating: 5.0 dc volts Mounting Facility Type And Quantity: 6 terminal Features Provided: Active Insertion Loss At Reference Frequency Per Function In Decibels: 3.0 blank Functional Terminal Type And Quantity: 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function Body Material: Metal Frequency Band Width Per Function: 49.188 kilohertz blank and 50.812 kilohertz blank Discrimination At Specificationified Frequencies Per Function In Decibels:

N/a

NSN 5915-01-350-7391

Band Pass Filter - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0

