

View Online at <https://aerobasegroup.com/nsn/5915-01-350-7396>

Overall Length:

5.340 inches

Body Length:

3.250 inches

Body Width:

3.370 inches

Body Height:

1.530 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 3.735 inches and 3.765 inches

End Application:

Milstar/stc d

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

50.0 1st radio interference 50.0 2nd radio interference

Operating Current Rating Per Function In Amps:

20.0 1st radio interference 20.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Nut

Functional Terminal Type And Quantity:

2 threaded stud input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2.25 kilovolts at sea level

Body Surface Treatment:

Tin

Special Features:

Two filtered functions

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0