

View Online at <https://aerobasegroup.com/nsn/5915-01-350-7396>

**Overall Length:**

5.340 inches

**Body Length:**

3.250 inches

**Body Width:**

3.370 inches

**Body Height:**

1.530 inches

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 3.735 inches and 3.765 inches

**End Application:**

Milstar/stc d

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

50.0 1st radio interference 50.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

20.0 1st radio interference 20.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Features Provided:**

Nut

**Functional Terminal Type And Quantity:**

2 threaded stud input 1st function 2 threaded stud output 2nd function 1 threaded stud ground 3rd function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

2.25 kilovolts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Two filtered functions

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0