

View Online at <https://aerobasegroup.com/nsn/5915-01-350-7397>

**Overall Length:**

1.123 inches

**Overall Height:**

1.550 inches

**Overall Width:**

1.970 inches

**Body Length:**

0.810 inches

**Body Width:**

1.175 inches

**Unthreaded Mounting Hole Diameter:**

0.132 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.580 inches

**End Application:**

4935-01-262-0017

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

440.0 1st radio interference 440.0 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.0 1st radio interference 3.0 2nd radio interference

**Maximum Voltage Drop Per Function:**

2.5 volts ac 1st radio interference 2.5 volts ac 2nd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference

**Input Terminal Manufacturer Code:**

02777

**Input Terminal Identification:**

Sma-receptacle

**Maximum Temperature Rise:**

25.0 degrees celsius

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 2 tab, solder lug output 2nd function 1 tab, solder lug ground 3rd function

**Operating Voltage Rating And Type Per Function:**

250.0 volts ac 1st radio interference 1st function 250.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

2.25 kilovolts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

Two filtered functions

**Style Designator:**

Rectangular terminal/terminals on adjacent surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0