

View Online at <https://aerobasegroup.com/nsn/5915-01-353-2859>

**Unthreaded Mounting Hole Diameter:**

0.235 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.290 inches

**Vibration Resistance Range In Hertz:**

+10.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.600 inches

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Average Life Rating In Hours:**

200000.0

**End Application:**

Valve-selecti

**Source Impedance Rating Per Function:**

50.0 ohms 3rd radio interference

**Load Impedance Per Function:**

50.0 ohms 2nd radio interference

**Power Line Frequency Rating Per Function In Hertz:**

400.0 3rd radio interference

**Operating Current Rating Per Function In Amps:**

2.5 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.15 volts ac 3rd radio interference

**Principal Circuitry Type Per Function:**

Inductance-capacitance 3rd radio interference

**Maximum Temperature Rise:**

45.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Functional Terminal Type And Quantity:**

3 threaded stud input 1st function

**Operating Voltage Rating And Type Per Function:**

115.0 volts ac 3rd radio interference 3rd function

**Body Material:**

Aluminum

**Body Surface Treatment:**

Tin

**Special Features:**

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:**

Hardened

**Unpackaged Unit Weight:**

1.500 pounds

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0