

View Online at <https://aerobasegroup.com/nsn/5915-01-353-8643>

Overall Length:

2.714 inches

Overall Height:

0.983 inches

Overall Width:

0.479 inches

Unthreaded Mounting Hole Diameter:

0.122 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.506 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Uhf/receiver

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Operating Current Rating Per Function In Amps:

5.0 1st radio interference5.0 2nd radio interference5.0 3rd radio interference5.0 4th radio interference5.0 5th radio interference5.0 6th radio interference

Maximum Voltage Drop Per Function:

2.0 volts dc 1st radio interference2.0 volts dc 2nd radio interference5.0 volts dc 3rd radio interference2.0 volts dc 4th radio interference2.0 volts dc 5th radio interference2.0 volts dc 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

37 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

200.0 volts dc 1st radio interference 1st function200.0 volts dc 2nd radio interference 2nd function200.0 volts dc 3rd radio interference 3rd function50.0 volts dc 4th radio interference 4th function200.0 volts dc 5th radio interference 5th function200.0 volts dc 6th radio interference 6th function

Special Features:

37 filtered functions

Style Designator:

Filter connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0