

View Online at <https://aerobasegroup.com/nsn/5915-01-354-4729>

**Overall Length:**

5.376 inches

**Body Length:**

3.500 inches

**Body Outside Diameter:**

1.125 inches

**Vibration Resistance Range In Hertz:**

+1.0/+2000.0

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**End Application:**

Fastcal

**Reference Frequency Per Function:**

15.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

21377

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

21377

**Output Terminal Identification:**

Sma-plug

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

5.0 watts blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Features Provided:**

Shock resistant

**Insertion Loss At Reference Frequency Per Function In Decibels:**

3.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 1 connector, plug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

3.00 kilohertz blank and 15.00 megahertz blank and 22.50 megahertz blank and 30.00 megahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

3.00 kilohertz blank and 15.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 50.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

3.0 kilohertz blank and 15.0 megahertz blank

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0