

View Online at <https://aerobasegroup.com/nsn/5915-01-354-6109>

**Overall Length:**

2.500 inches

**Body Outside Diameter:**

0.375 inches

**Operating Temperature Range:**

-55.0/+150.0 degrees celsius

**End Application:**

Fastcal

**Reference Frequency Per Function:**

12.0 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Input Terminal Manufacturer Code:**

00929

**Input Terminal Identification:**

Sma-receptacle

**Output Terminal Manufacturer Code:**

00929

**Output Terminal Identification:**

Sma-plug

**Voltage Standing Wave Ratio Per Function:**

1.7 blank

**Average Power Rating Per Function:**

50.0 watts blank

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.2 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function1 connector, plug output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

4.80 gigahertz blank and 12.00 gigahertz blank and 14.40 gigahertz blank and 18.00 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

4.80 gigahertz blank and 12.00 megahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

1.0 blank and 55.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

4.8 gigahertz blank and 12.0 gigahertz blank

**Unpackaged Unit Weight:**

3.000 ounces

**Precious Material And Location:**

Body surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0