

View Online at <https://aerobasegroup.com/nsn/5915-01-356-1360>

**Overall Height:**

0.700 inches

**Body Length:**

1.000 inches

**Body Width:**

0.500 inches

**Body Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.380 inches

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Average Life Rating In Hours:**

100000.0

**End Application:**

Lantirn navigation pod

**Reference Frequency Per Function:**

60.0 megahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Average Power Rating Per Function:**

1.0 watts blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

6 pin

**Features Provided:**

Bessel response

**Insertion Loss At Reference Frequency Per Function In Decibels:**

60.0 blank

**Functional Terminal Type And Quantity:**

4 pin ground and 2 pin input-output

**Frequency Band Width Per Function:**

65.50 megahertz blank and 54.50 megahertz blank

**Maximum Dielectric Withstanding Dc Voltage:**

20.0 volts at sea level

**Special Features:**

Selected item drawing; selected from: 50140 mb3ib20-60/5.0-p/p; 67021 mfx-3-60-5.0-p/p

**Style Designator:**

Rectangular terminal/terminals on one surface

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0