

View Online at <https://aerobasegroup.com/nsn/5915-01-356-4194>

Overall Length:

2.088 inches

Overall Height:

1.040 inches

Overall Width:

1.675 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.852 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

End Application:

Intercom set

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference50.0 ohms 2nd radio interference50.0 ohms 3rd radio interference50.0 ohms 4th radio interference50.0 ohms 5th radio interference50.0 ohms 6th radio interference

Operating Current Rating Per Function In Amps:

5.0 1st radio interference5.0 2nd radio interference5.0 3rd radio interference5.0 4th radio interference5.0 5th radio interference5.0 6th radio interference

Maximum Voltage Drop Per Function:

2.0 volts dc 1st radio interference5.0 volts dc 2nd radio interference5.0 volts dc 3rd radio interference5.0 volts dc 4th radio interference5.0 volts dc 5th radio interference5.0 volts dc 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 5th radio interference inductance-capacitance 6th radio interference

Maximum Tempurature Rise:

25.0 degrees celsius

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Corrosion resistant and moisture resistant

Functional Terminal Type And Quantity:

25 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

200.0 volts dc 1st radio interference 1st function200.0 volts dc 2nd radio interference 2nd function200.0 volts dc 3rd radio interference 3rd function200.0 volts dc 4th radio interference 4th function200.0 volts dc 5th radio interference 5th function200.0 volts dc 6th radio interference 6th function

Body Surface Treatment:

Tin

Special Features:

25 filtered functions

Style Designator:

Filter connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A047b0