

View Online at <https://aerobasegroup.com/nsn/5915-01-357-3303>

Overall Length:

2.140 inches

Overall Height:

1.562 inches

Overall Width:

1.250 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

1520-01-298-4532 brace, bomb rack

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference 50.0 ohms 3rd radio interference 50.0 ohms 4th radio interference 50.0 ohms 5th radio interference 50.0 ohms 6th radio interference

Power Line Frequency Rating Per Function In Hertz:

425.0 1st radio interference 425.0 2nd radio interference 425.0 3rd radio interference 425.0 4th radio interference 425.0 5th radio interference 425.0 6th radio interference

Operating Current Rating Per Function In Amps:

32.0 1st radio interference 32.0 2nd radio interference 32.0 3rd radio interference 32.0 4th radio interference 1.5 5th radio interference 1.5 6th radio interference

Principal Circuitry Type Per Function:

Inductance-capacitance 1st radio interference inductance-capacitance 2nd radio interference inductance-capacitance 3rd radio interference inductance-capacitance 4th radio interference inductance-capacitance 3rd radio interference inductance-capacitance 6th radio interference

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

4 unthreaded hole

Functional Terminal Type And Quantity:

12 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

180.0 volts ac 1st radio interference 1st function and 500.0 volts dc 1st radio interference 1st function 180.0 volts ac 2nd radio interference 2nd function and 500.0 volts dc 2nd radio interference 2nd function 180.0 volts ac 3rd radio interference 3rd function and 500.0 volts dc 3rd radio interference 3rd function 180.0 volts ac 4th radio interference 4th function and 500.0 volts dc 4th radio interference 4th function 180.0 volts ac 5th radio interference 5th function and 500.0 volts dc 5th radio interference 5th function 180.0 volts ac 6th radio interference 6th function and 500.0 volts dc 6th radio interference 6th function

Body Material:

Metal

Precious Material:

Silver

Style Designator:

Filter connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A047b0