

View Online at <https://aerobasegroup.com/nsn/5915-01-357-9468>

**Overall Length:**

3.675 inches

**Vibration Resistance Range In Hertz:**

+50.0/+1000.0

**Operating Temperature Range:**

-40.0/+95.0 degrees celsius

**Average Life Rating In Hours:**

200000.0

**End Application:**

Receiving set, countermeasures an/alr-56

**Reference Frequency Per Function:**

5.0 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.3 blank

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 terminal

**Insertion Loss At Reference Frequency Per Function In Decibels:**

0.75 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.00 gigahertz blank and 5.00 gigahertz blank and 10.00 gigahertz blank and 15.00 gigahertz blank

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.00 gigahertz blank and 5.00 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.0 gigahertz blank and 5.0 gigahertz blank

**Special Features:**

Electrostatic discharge sensitive

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0