

View Online at <https://aerobasegroup.com/nsn/5915-01-358-0846>

Overall Length:

1.650 inches

Body Length:

0.800 inches

Body Width:

0.400 inches

Body Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.360 inches

Operating Temperature Range:

-40.0/+95.0 degrees celsius

Average Life Rating In Hours:

20000.0

End Application:

Receiving set, countermeasures an/alr-56

Reference Frequency Per Function:

1.35 gigahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Voltage Standing Wave Ratio Per Function:

1.5 blank

Mounting Facility Screw Thread Series Designator:

Unc

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

2 threaded hole

Insertion Loss At Reference Frequency Per Function In Decibels:

1.0 blank

Functional Terminal Type And Quantity:

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function

Specified Frequencies Of Discrimination Per Function:

1.70 gigahertz blank and 1.98 gigahertz blank and 2.66 gigahertz blank and 4.01 gigahertz blank

Thread Size:

0.086 inches

Body Material:

Metal

Frequency Band Width Per Function:

1.98 gigahertz blank and 2.66 gigahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 60.0 blank

Voltage Standing Wave Ratio Frequency Limits Per Function:

1.98 gigahertz blank and 2.66 gigahertz blank

Unpackaged Unit Weight:

1.500 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0