

View Online at <https://aerobasegroup.com/nsn/5915-01-358-0846>

**Overall Length:**

1.650 inches

**Body Length:**

0.800 inches

**Body Width:**

0.400 inches

**Body Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.360 inches

**Operating Temperature Range:**

-40.0/+95.0 degrees celsius

**Average Life Rating In Hours:**

20000.0

**End Application:**

Receiving set, countermeasures an/alr-56

**Reference Frequency Per Function:**

1.35 gigahertz blank

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Principal Circuitry Type Per Function:**

Inductance-capacitance blank

**Voltage Standing Wave Ratio Per Function:**

1.5 blank

**Mounting Facility Screw Thread Series Designator:**

Unc

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Insertion Loss At Reference Frequency Per Function In Decibels:**

1.0 blank

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function1 connector, receptacle output 2nd function

**Specified Frequencies Of Discrimination Per Function:**

1.70 gigahertz blank and 1.98 gigahertz blank and 2.66 gigahertz blank and 4.01 gigahertz blank

**Thread Size:**

0.086 inches

**Body Material:**

Metal

**Frequency Band Width Per Function:**

1.98 gigahertz blank and 2.66 gigahertz blank

**Discrimination At Specificationified Frequencies Per Function In Decibels:**

3.0 blank and 60.0 blank

**Voltage Standing Wave Ratio Frequency Limits Per Function:**

1.98 gigahertz blank and 2.66 gigahertz blank

**Unpackaged Unit Weight:**

1.500 ounces

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0