NSN 5915-01-358-1057

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-358-1057

Overall Length:
6.750 inches
Overall Height:
6.000 inches
Body Length:
5.350 inches
Body Width:
4.850 inches
Body Height:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
6.000 inches
Vibration Resistance Range In Hertz:
+15.0/+2000.0
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
5.500 inches
Operating Tempurature Range:
-65.0/+160.0 degrees celsius
Average Life Rating In Hours:
Average Life Rating In Hours: 13500.0
13500.0
13500.0 End Application:
13500.0 End Application: Fuel system 1
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function:
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function:
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps:
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function:
13500.0 End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank
End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank Principal Circuitry Type Per Function:
End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank
End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Inclosure Type:
End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Inclosure Type: Encased
End Application: Fuel system 1 Source Impedance Rating Per Function: 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank Operating Current Rating Per Function In Amps: 1.0 blank Maximum Voltage Drop Per Function: 0.28 volts dc blank Principal Circuitry Type Per Function: Inductance-capacitance blank Inclosure Type: Encased Mounting Facility Type And Quantity:

Functional Terminal Type And Quantity:

2 connector, receptacle input 1st function1 connector, receptacle output 2nd function

NSN 5915-01-358-1057

Radio Frequency Interference Filter - Page 2 of 2



Operating Voltage Rating And Type Per Function:
28.0 volts dc blank
Body Material:
Metal
Maximum Dielectric Withstanding Dc Voltage:
1.5 kilovolts at sea level
Body Surface Treatment:
Cadmium
Unpackaged Unit Weight:
3.750 pounds
Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A047b0