

View Online at <https://aerobasegroup.com/nsn/5915-01-358-2466>

**Overall Length:**

5.250 inches

**Overall Height:**

2.000 inches

**Overall Width:**

7.250 inches

**Body Length:**

3.250 inches

**Body Width:**

6.000 inches

**Unthreaded Mounting Hole Diameter:**

0.375 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.000 inches

**Vibration Resistance Range In Hertz:**

+20.0/+2000.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

4.250 inches

**Operating Temperature Range:**

+0.0/+50.0 degrees celsius

**End Application:**

Ltwgt shf sat

**Source Impedance Rating Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Load Impedance Per Function:**

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

**Operating Current Rating Per Function In Amps:**

3.5 1st radio interference 3.5 2nd radio interference

**Maximum Voltage Drop Per Function:**

1.2 volts ac 1st radio interference 1.2 volts ac 2nd radio interference

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Features Provided:**

Shock resistant

**Functional Terminal Type And Quantity:**

1 connector, receptacle input 1st function 1 connector, receptacle output 2nd function 1 threaded stud ground 3rd function

**Operating Voltage Rating And Type Per Function:**

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

**Body Material:**

Metal

**Body Surface Treatment:**

Tin

**Special Features:**

Two filtered functions

**Unpackaged Unit Weight:**

4.000 pounds

**Style Designator:**

Rectangular terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A047b0