## NSN 5915-01-361-6316

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-361-6316

## **Overall Height:** 0.875 inches **Body Length:** Between 1.485 inches and 1.515 inches **Body Width:** Between 0.985 inches and 1.015 inches **Body Height:** Between 0.485 inches and 0.515 inches Vibration Resistance Range In Hertz: +5.0/+200.0 **Operating Tempurature Range:** -35.0/+85.0 degrees celsius **End Application:** 5895-01-180-1415 control, computer **Reference Frequency Per Function:** 21.4 megahertz blank **Source Impedance Rating Per Function:** 50.0 ohms blank Load Impedance Per Function: 50.0 ohms blank **Principal Circuitry Type Per Function:** Inductance-capacitance blank **Voltage Standing Wave Ratio Per Function:** 3.0 blank **Inclosure Type:** Hermetically sealed Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 2.5 blank **Functional Terminal Type And Quantity:** 1 pin input 1st function1 pin output 2nd function2 pin ground 3rd function **Specified Frequencies Of Discrimination Per Function:** 20.76 megahertz blank and 21.08 megahertz blank and 21.72 megahertz blank and 22.04 megahertz blank **Body Material:** Metal **Frequency Band Width Per Function:** 21.08 megahertz blank and 21.72 megahertz blank **Discrimination At Specificationified Frequencies Per Function In Decibels:** 3.0 blank and 40.0 blank Voltage Standing Wave Ratio Frequency Limits Per Function:

21.08 megahertz blank and 21.72 megahertz blank

## NSN 5915-01-361-6316

Band Pass Filter - Page 2 of 2



Style Designator:

Rectangular terminal/terminals on one surface

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A047b0