NSN 5915-01-370-0918

Band Pass Filter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5915-01-370-0918

1.281 inches Body Length: Between 1.157 inches and 1.219 inches Body Width: Between 1.157 inches and 1.219 inches Body Width: Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Pacility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function in Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 181349-mill-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-18327/46 government specification Shelf Life: Na Unit of Measure: — Demilitarization: No Flig: A04750	Overall Height:
Boty Length: Botwean 1.157 inches and 1.219 inches Body Width: Botwean 1.157 inches and 1.219 inches Body Height: Between 0.405 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81348-Wil-18327/46 government specification No Bullitarization: No Filig:	
Body Width: Between 1.157 inches and 1.219 inches Body Width: Between 1.157 inches and 1.219 inches Body Height: Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 1300.0 obms blank Load Impedance Per Function: 1000.0 obms blank Functional Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-1-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-1-18327/46 government specification Shelf Life: Na Unit Of Measure: - Demilitarization: No Filig:	
Between 1.157 inches and 1.219 inches Body Height: Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Locad Impedance Per Function: 10000.0 ohms blank Inciosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 8.0 blank Functional Terminal Type And Quantity: 4 wine load input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-f18327/86 government specification Shelf Life: N/a Unit Of Measure:	
Between 1.157 inches and 1.219 inches Body Height: Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 1000.0 ohms blank Load Impedance Per Function: 1000.0 ohms blank Load Impedance Per Function: 1000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 virie lead input-output 7 requency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminalterminals on one surface Test Data Document: 81349-mil-11-8227 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-1-18227 specification fincludes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-1-18227 specification Sheft Life: No Unit Of Measure:	
Body Height: Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Incapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-4-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	
Between 0.406 inches and 0.531 inches Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Wildth Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-1-13327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-Wil-1-18327/46 government specification Shelf Life: N/a Unit Of Measure:	
Reference Frequency Per Function: 1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-I-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-will-I-18327/46 government specification Shelf Life: Na Unit Of Measure:	
1300.0 hertz blank Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mill-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kill-f-18327/46 government specification Shelf Life: N/a Unit Of Measure:	
Source Impedance Rating Per Function: 10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	
10000.0 ohms blank Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mill-f18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-#ill-f18327/46 government specification Shelf Life: V/a Unit Of Measure: Demilitarization: No Filg:	
Load Impedance Per Function: 10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-Ril-18327/46 government specification Sheft Life: N/a Unit Of Measure:	
10000.0 ohms blank Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-wil-f-18327/46 government specification Na Unit Of Measure:	
Inclosure Type: Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-1-8327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Encapsulated Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mill-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Mounting Facility Type And Quantity: 4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure:	
4 terminal Insertion Loss At Reference Frequency Per Function In Decibels: 6.0 blank Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Insertion Loss At Reference Frequency Per Function In Decibels:
Functional Terminal Type And Quantity: 4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
4 wire lead input-output Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Functional Terminal Type And Quantity:
Frequency Band Width Per Function: 1202.00 hertz blank and 1398.00 hertz blank Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	4 wire lead input-output
Style Designator: Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Rectangular terminal/terminals on one surface Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1202.00 hertz blank and 1398.00 hertz blank
Test Data Document: 81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rectangular terminal/terminals on one surface
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-f-18327 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-kil-f-18327/46 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-kil-f-18327/46 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A047b0	Fiig:
	A047b0