

View Online at <https://aerobasegroup.com/nsn/5915-01-372-8509>

Overall Length:

Between 4.695 inches and 4.705 inches

Overall Height:

0.625 inches

Body Length:

Between 4.695 inches and 4.705 inches

Body Width:

Between 1.245 inches and 1.255 inches

Unthreaded Mounting Hole Diameter:

Between 0.133 inches and 0.143 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 4.447 inches and 4.453 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.997 inches and 1.003 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Reference Frequency Per Function:

5.8999 megahertz blank

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

5 unthreaded hole

Features Provided:

Shock resistant and moisture resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.2 blank

Functional Terminal Type And Quantity:

1 wire lead input 1st function 1 wire lead output 2nd function 2 wire lead ground 3rd function

Specified Frequencies Of Discrimination Per Function:

8.20 megahertz blank and 11.80 megahertz blank

Frequency Band Width Per Function:

4.10 megahertz blank and 5.8999 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 26.0 blank

Unpackaged Unit Weight:

3.500 ounces

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0