## NSN 5915-01-372-8510

Low Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-372-8510

**Overall Length:** 

Between 4.695 inches and 4.705 inches

**Overall Height:** 

0.625 inches

**Body Length:** 

Between 4.695 inches and 4.705 inches

**Body Width:** 

Between 1.245 inches and 1.255 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.133 inches and 0.143 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

Between 4.447 inches and 4.453 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.997 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Reference Frequency Per Function:** 

8.3999 megahertz blank

**Source Impedance Rating Per Function:** 

50.0 ohms blank

**Load Impedance Per Function:** 

50.0 ohms blank

**Principal Circuitry Type Per Function:** 

Inductance-capacitance blank

Inclosure Type:

Encased

**Mounting Facility Type And Quantity:** 

5 unthreaded hole

**Features Provided:** 

Shock resistant and moisture resistant

Insertion Loss At Reference Frequency Per Function In Decibels:

0.2 blank

**Functional Terminal Type And Quantity:** 

1 wire lead input 1st function1 wire lead output 2nd function2 wire lead ground 3rd function

**Specified Frequencies Of Discrimination Per Function:** 

11.80 megahertz blank and 16.80 megahertz blank

**Frequency Band Width Per Function:** 

5.90 megahertz blank and 8.3999 megahertz blank

Discrimination At Specificationified Frequencies Per Function In Decibels:

3.0 blank and 26.0 blank

**Unpackaged Unit Weight:** 

3.500 ounces

## NSN 5915-01-372-8510

Low Pass Filter - Page 2 of 2



Style Designator:
Rectangular terminal/terminals on opposite surfaces
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A047b0