

View Online at <https://aerobasegroup.com/nsn/5915-01-376-1994>

Overall Length:

31.186 inches

Body Length:

28.000 inches

Body Width:

16.000 inches

Body Height:

5.750 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

17.280 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

14.000 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Load Impedance Per Function:

50.0 ohms 1st radio interference 50.0 ohms 2nd radio interference

Power Line Frequency Rating Per Function In Hertz:

60.0 1st radio interference 60.0 2nd radio interference

Operating Current Rating Per Function In Amps:

60.0 1st radio interference 60.0 2nd radio interference

Maximum Voltage Drop Per Function:

1.1 volts ac 1st radio interference 1.1 volts ac 2nd radio interference

Maximum Temperature Rise:

25.0 degrees celsius

Full Load Insertion Loss Frequencies In Megahertz:

0.15 and 0.1 and 0.5 and 1.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

20.0 and 40.0 and 50.0 and 60.0 and 60.0 and 60.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

26 unthreaded hole

Features Provided:

Heat resistant and shock resistant and moisture resistant

Functional Terminal Type And Quantity:

2 tab, solder lug input 1st function 2 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

120.0 volts ac 1st radio interference 1st function 120.0 volts ac 2nd radio interference 2nd function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

2200.0 volts at sea level

Body Surface Treatment:

Tin

Unpackaged Unit Weight:

15.000 pounds

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0