

View Online at <https://aerobasegroup.com/nsn/5915-01-380-1076>

Overall Length:

1.250 inches

Body Length:

0.648 inches

Body Outside Diameter:

0.416 inches

Vibration Resistance Range In Hertz:

+10.0/+2000.0

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms blank

Load Impedance Per Function:

50.0 ohms blank

Power Line Frequency Rating Per Function In Hertz:

400.0 blank

Operating Current Rating Per Function In Amps:

1.0 blank

Maximum Voltage Drop Per Function:

0.25 volts ac blank

Principal Circuitry Type Per Function:

Inductance-capacitance blank

Maximum Temperature Rise:

25.0 degrees celsius

Mounting Facility Screw Thread Series Designator:

Unf

Inclosure Type:

Hermetically sealed

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Shock resistant

Functional Terminal Type And Quantity:

1 tab, solder lug output 2nd function

Operating Voltage Rating And Type Per Function:

125.0 volts ac blank and 150.0 volts dc blank

Thread Size:

0.250 inches

Body Material:

Metal

Style Designator:

Round terminal/terminals on opposite surfaces

Test Data Document:

81349-mil-f-15733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15733/26 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A047b0