

View Online at <https://aerobasegroup.com/nsn/5915-01-380-3197>

**Overall Length:**

0.750 inches

**Body Length:**

0.430 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms blank

**Load Impedance Per Function:**

50.0 ohms blank

**Power Line Frequency Rating Per Function In Hertz:**

60.0 blank

**Operating Current Rating Per Function In Amps:**

15.0 blank

**Principal Circuitry Type Per Function:**

Capacitance-inductance blank

**Maximum Temperature Rise:**

25.0 degrees celsius

**Full Load Insertion Loss Frequencies In Megahertz:**

1.0 and 10.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

6.0 and 25.0 and 50.0

**Mounting Facility Screw Thread Series Designator:**

Unf

**Inclosure Type:**

Hermetically sealed

**Width Across Flats:**

0.200 inches

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Shock resistant and moisture resistant

**Functional Terminal Type And Quantity:**

1 tab, solder lug output 2nd function

**Operating Voltage Rating And Type Per Function:**

125.0 volts ac blank and 200.0 volts dc blank

**Thread Size:**

0.250 inches

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

400.0 volts at sea level

**Style Designator:**

Round terminal/terminals on opposite surfaces

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A047b0