NSN 5915-01-381-8413

Band Pass Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-381-8413

Overall Length:
8.220 inches
Body Length:
7.500 inches
Body Width:
1.500 inches
Body Height:
1.000 inches
Operating Tempurature Range:
-30.0/+140.0 degrees celsius
Reference Frequency Per Function:
113.5 megahertz blank
Source Impedance Rating Per Function:
50.0 ohms blank
Load Impedance Per Function:
50.0 ohms blank
Principal Circuitry Type Per Function:
Inductance-capacitance blank
Voltage Standing Wave Ratio Per Function:
1.5 blank
Mounting Facility Screw Thread Series Designator:
Mounting Facility Screw Thread Series Designator: Unc
Unc
Unc Inclosure Type:
Unc Inclosure Type: Hermetically sealed
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank Thread Size: 0.112 inches
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank Thread Size: 0.112 inches Body Material:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank Thread Size: 0.112 inches Body Material: Aluminum
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank Thread Size: 0.112 inches Body Material: Aluminum Frequency Band Width Per Function:
Unc Inclosure Type: Hermetically sealed Mounting Facility Type And Quantity: 4 threaded hole Insertion Loss At Reference Frequency Per Function In Decibels: 1.0 blank Functional Terminal Type And Quantity: 1 connector, receptacle output 2nd function Specified Frequencies Of Discrimination Per Function: 98.00 megahertz blank and 104.00 megahertz blank and 125.00 megahertz blank and 144.00 megahertz blank Thread Size: 0.112 inches Body Material: Aluminum Frequency Band Width Per Function: 104.00 megahertz blank and 125.00 megahertz blank and 125.00 megahertz blank

104.0 megahertz blank and 125.0 megahertz blank

NSN 5915-01-381-8413

Band Pass Filter - Page 2 of 2



Body Surface Treatment:

Silver

Precious Material And Location:

Body surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular terminal/terminals on opposite surfaces

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0