

View Online at https://aerobasegroup.com/nsn/5915-01-390-0125

| Overall Length: |
|---|
| 1.666 inches |
| Overall Height: |
| 0.938 inches |
| Overall Width: |
| 0.938 inches |
| Mounting Slot Width: |
| Between 0.122 inches and 0.134 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.719 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.719 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Source Impedance Rating Per Function: |
| 50.0 ohms 4th radio interference |
| Load Impedance Per Function: |
| 50.0 ohms 5th radio interference |
| Power Line Frequency Rating Per Function In Hertz: |
| 60.0 3rd radio interference |
| Operating Current Rating Per Function In Amps: |
| 3.0 2nd radio interference |
| Inclosure Type: |
| Encased |
| Mounting Facility Type And Quantity: |
| 4 slot |
| Features Provided: |
| Moisture resistant and shock resistant |
| Functional Terminal Type And Quantity: |
| 6 friction w/grounding strap and pin input-output |
| Operating Voltage Rating And Type Per Function: |
| 200.0 volts ac 6th radio interference 6th function and 200.0 volts dc 6th radio interference 6th function |
| Body Material: |
| Aluminum |
| Maximum Dielectric Withstanding Dc Voltage: |
| 500.0 volts at sea level |
| Body Surface Treatment: |
| Cadmium or nickel |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material: |
| Gold |



Style Designator:

Filter connector

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A047b0