

View Online at <https://aerobasegroup.com/nsn/5915-01-390-3462>

**Overall Length:**

Between 2.073 inches and 2.103 inches

**Overall Height:**

0.932 inches

**Overall Width:**

Between 0.479 inches and 0.529 inches

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 1.847 inches and 1.857 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Source Impedance Rating Per Function:**

50.0 ohms 4th radio interference

**Load Impedance Per Function:**

50.0 ohms 5th radio interference

**Operating Current Rating Per Function In Amps:**

5.0 3rd radio interference

**Full Load Insertion Loss Frequencies In Megahertz:**

30.0 and 100.0 and 1000.0

**Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:**

8.0 and 25.0 and 50.0

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Functional Terminal Type And Quantity:**

25 friction w/grounding strap and pin input-output

**Operating Voltage Rating And Type Per Function:**

200.0 volts dc 4th radio interference 4th function

**Body Material:**

Metal

**Maximum Dielectric Withstanding Dc Voltage:**

500.0 volts at sea level

**Body Surface Treatment:**

Tin

**Special Features:**

25 filtered functions

**Precious Material And Location:**

Ground spring surfaces silver and contact surfaces gold

**Precious Material:**

Gold and silver

**Style Designator:**

Filter connector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A047b0