NSN 5915-01-390-3462

Radio Frequency Interference Filter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5915-01-390-3462

Overall Length:

Between 2.073 inches and 2.103 inches

Overall Height:

0.932 inches

Overall Width:

Between 0.479 inches and 0.529 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.847 inches and 1.857 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Source Impedance Rating Per Function:

50.0 ohms 4th radio interference

Load Impedance Per Function:

50.0 ohms 5th radio interference

Operating Current Rating Per Function In Amps:

5.0 3rd radio interference

Full Load Insertion Loss Frequencies In Megahertz:

30.0 and 100.0 and 1000.0

Full Load Minimum Insertion Loss At Specificationified Frequency In Decibels:

8.0 and 25.0 and 50.0

Inclosure Type:

Encased

Mounting Facility Type And Quantity:

2 unthreaded hole

Functional Terminal Type And Quantity:

25 friction w/grounding strap and pin input-output

Operating Voltage Rating And Type Per Function:

200.0 volts dc 4th radio interference 4th function

Body Material:

Metal

Maximum Dielectric Withstanding Dc Voltage:

500.0 volts at sea level

Body Surface Treatment:

Tin

Special Features:

25 filtered functions

Precious Material And Location:

Ground spring surfaces silver and contact surfaces gold

Precious Material:

Gold and silver

NSN 5915-01-390-3462

Radio Frequency Interference Filter - Page 2 of 2



Style Designator:
Filter connector
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A047b0